

polymer in ag to disperse asa in pulp allowing retention on fibre.

DC A14 A97 F09 P42

IN BRESLIN, M D; RENDE, D S

PA (NALC) NALCO CHEM CO

CYC 1

PI US 4657946 A 19870414 (198717)\* 10p

ADT US 4657946 A US 1985-755503 19850716

PRAI US 1984-574324 19840127; US 1984-625476 19840625; US 1985-755503 19850716

IC B05D003-02; D21D003-00

AB US 4657946 A UPAB: 19950602

Preparation of sized paper prods. involves the use of an effective amount of emulsified alkenyl succinic anhydride (ASA) sizing agent (I). (I) contains water, ASA, surfactants (II) and a cationic polymer (III), the active ASA to active cationic polymer weight ratio being 1:1-15:1 (2:1-15:1). (II) is 0-2 weight% of phosphated ethoxylate or sulphonated emulsifier whilst (III) is a water soluble cationic vinyl polymer of mol. weight below 1,000,000 (10,000-100,000). A pre-application agitation of (I) is conducted to obtain particles of ASA not exceeding 5 micron in dia. and a method of sizing paper is also claimed.

USE/ADVANTAGE - (I) is useful in the sizing of cellulosic materials. (III) provides improved emulsification of ASA to disperse it in the pulp and allow retention of the zinc onto the fibre. As a result machine deposits and continuity problems are removed leading to greater emulsion stability in storage. Sized paper prods. prepared using (I) have good ink holdout.

0/1

Dwg. 0/1

FS CPI GMPI

FA AB

MC CPI: A10-E07; A10-E20; A12-W06; F05-A06C; F05-A06D

L9 ANSWER 39 OF 56 WPIDS (C) 2002 THOMSON DERWENT

AN 1987-017628 [03] WPIDS Full-text

DNC C1987-007109

TI Production of emulsion for sizing in paper-making process - by mixing sizing agents with aqueous emulsifier solution and mixing prod. with water.

DC A14 A97 F09

PA (IDEM) IDEMITSU PETROCHEM CO

CYC 1

PI JP 61274735 A 19861204 (198703)\* 6p

ADT JP 61274735 A JP 1985-117345 19850529

PRAI JP 1985-117345 19850529

IC B01J013-00; D21H003-08

AB JP 61274735 A UPAB: 19930922

Sizing agents (1) and an aqueous solution containing 20-70wt.% of emulsifiers (2) are mixed; then resultant mixture is mixed with water to produce the emulsion. Pref. (1) are substd. cyclic dicarboxylic anhydrides of formula (I), where R1 is a dimethylene or trimethylene gp.; and R2 is an alkyl, alkenyl, aralkyl, or aralkenyl gp.; (2) are pref. anionic, cationic, or nonionic emulsifiers.

ADVANTAGE - The emulsion can be produced in a short time. Thus produced emulsions provide paper having good sizing effects.

An example of the emulsion was produced by adding a mixture of 5g alkenyl succinic anhydride and 1.43g of an aqueous solution